



Material:
* Contact: Brass

Ordering Code

CH71 ** * H * **
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Plating Code:
 - 1= 3.05 μ m(120 μ "") Min. Tin over 0.76 μ m(30 μ "") Nickel
 - 2= Gold flash plated over 1.27 μ m(50 μ "") Nickel
 - 3= 0.38 μ m(15 μ "") Gold plated over 1.27 μ m(50 μ "") Nickel
 - 4= 0.76 μ m(30 μ "") Gold plated over 1.27 μ m(50 μ "") Nickel
- ④ H= Right angle
- ⑤ Insulation:
 - 1= PBT UL 94V-0, Color Black (ROHS Compliant)
 - A= Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option cord:
See Table PDF. File No. CH7102T

A = 2.00 * No. of Spaces
 B = A + 2.00
 * Available in 4 through 80 circuits

Recommended P.C. Board Layout

④	Sun	7/29-08'	ECN08359			DATE	UNIT: mm / inch	TITLE: 2.00MM(.079") RIGHT ANGLE	 瀚荃股份有限公司 CviLux Corporation	
③	Sun	1/19/06'	ECN06019		DRAWN BY: Sun	7/29-08'	TOLERANCE UNLESS OTHERWISE SPECIFIED	DUAL ROW BOARD MOUNT PIN HEADER		
②	Casey	5/28/04'	ECN04208		ENGINEER: Eisley	7/29-08'	.X ± 0.30 / .012 X' ± 1'	MATERIAL:		
①	SUN	4/09/04'	ECN04144		CHECKED BY: David	7/29-08'	.XX ± 0.20 / .008 .X' ±	FINISH:	DRAWING NO. CH7102SF	
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	7/29-08'	.XXX ± 0.10 / .004 .XX' ±		PART NO. CH71***H***	
								SCALE	4 / 1	SHEET 1 OF 1