

$A = 2.50 \times \text{No. of Spaces}$
 $B = A + 5.0$
 $C = A + 3.5$


* Available in 2 through 20 circuits

Material:
 * Insulation: Nylon 66 UL 94V-0
 Color Nature
 * Contact: Brass

Ordering Code:

$\frac{CI22}{①} \frac{**}{②} \frac{P}{③} \frac{*}{④} \frac{V}{⑤} \frac{K0}{⑥}$

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- △④ Plating option:
 1= 3.05μm(120μ") Min. Tin
 over 0.76μm(30μ") Nickel
 2= Gold flash plated over
 1.27μm(50μ") Nickel
- ⑤ Type: V= Straight
- ⑥ Other Option: K0= With Pin Kinked



Recommended P.C. Board Layout

RoHS Compliant

④						DATE	UNIT: mm / inch	TITLE: 2.50MM(.098")		
③					DRAWN BY: Sun	03/10-05'	TOLERANCE UNLESS OTHERWISE SPECIFIED	STRAIGHT PIN HEADERS		
②	SUN	3/10/05'	ECN05088		ENGINEER: Eisley	03/10-05'	.X ± 0.30/.012 X' ± r'	MATERIAL:		
①	SUN	3/05/04'	ECR04007-1/ECN04093		CHECKED BY: David	03/10-05'	.XX ± 0.20/.008 .X' ±	FINISH:		
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	03/10-05'	.XXX ± 0.10/.004 .XX' ±			
									DRAWING NO. CI2202SJ	PART NO. CI22**P*VK0
									SCALE 4 / 1	SHEET 1 OF 1